

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
5 April 2001 (05.04.2001)

PCT

(10) International Publication Number
WO 01/24137 A1


- (51) International Patent Classification⁷: G08G 1/123 48178 (US). BOCHENEK, Jeffrey, A. [US/US]; 4610 Windswept Drive, Milford, MI 48380 (US).
- (21) International Application Number: PCT/US00/26542
- (22) International Filing Date: 27 September 2000 (27.09.2000) (74) Agents: OBERHOLTZER, Steven, L.; Brinks Hofer Gilson & Lione, Suite 100, 1000 Victors Way, Ann Arbor, MI 48108 et al. (US).
- (25) Filing Language: English (81) Designated States (*national*): DE, GB, JP, US.
- (26) Publication Language: English (84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
- (30) Priority Data: 60/156,165 27 September 1999 (27.09.1999) US
- (71) Applicant (*for all designated States except US*): VISTEON GLOBAL TECHNOLOGIES, INC. [US/US]; Parklane Towers East, Suite 728, 1 Parklane Boulevard, Dearborn, MI 48126 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): ZORATTI, Paul, K. [US/US]; 13925 Monarch Drive, South Lyon, MI

Published:

- With international search report.
- Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: IMPACT SENSOR ASSEMBLY AND METHOD OF ATTACHING SAME TO A VEHICLE



(57) Abstract: An impact sensor assembly (46) provides a modular housing for vehicle impact sensors. The assembly comprises an impact sensor (42), an upper housing member (48), a lower housing member (50) and a connector (52) for establishing an electrical connection between the assembly and an appropriate vehicle system. The assembly may further include electronics (54) for processing signals received from the sensor (42). The lower housing member (50) receives and retains the sensor (42), and closely interacts with the upper housing member (48) to encase the sensor (42). The assembly (46) defines structural features that ensure its proper installation into a vehicle. The preferred embodiment assures proper functioning of deformation impact sensors. A method of installing the assembly provides a process for rapid and proper installation of the assembly (46) into a vehicle.

WO 01/24137 A1